

Interpon D1000 Textura[®]: Durability Test Report

The new Interpon Textura[®] is the ideal finish for powder coating surfaces where marring and wrap marking need to be eliminated. Our in-house laboratory analysis has proven Textura's durability and resilience across a number of tests against standard coatings.

Interpon D1000 Textura[®] Black outperformed a standard black matt / satin across three comparative durability tests – Abrasion Resistance Test (Weighted Panel to Panel Rub Test) [T980.7], Heated Wrap Marking Test and Cooling Properties Test.

Interpon Textura [®] Black	Standard black matt / satin
Test 1: Abrasion Resistance Test (Weighted Panel to Panel) [T980.7]	
Tested for: <ul style="list-style-type: none"> Abrasion 	
Summary Textura [®] Black performed 652 times better than standard black matt and satin products.	
Test 2: Heated Wrap Marking Test	
After 1 hour up to 120°C: <ul style="list-style-type: none"> No visible markings 	After 1 hour at 70°C: <ul style="list-style-type: none"> Visible markings and tiger striping
Summary Testing of Textura [®] Black stopped at 120°C due to bubble wrap melting / fusing. At this point, Textura [®] Black did not exhibit any markings.	Markings and tiger striping visible at 70°C.
Test 3: Cooling Properties Test (6mm steel panels, 20 minutes in 200°C)	
Out of oven for 12.5 minutes <ul style="list-style-type: none"> 65°C (Slightly cooler to the touch) 	Out of oven for 12.5 minutes <ul style="list-style-type: none"> 67°C
Summary Textura [®] Black reported 2°C cooler on the surface than standard black satin product.	

Global Trends on Textured Finishes

The Akzo Nobel global sales growth in textured powdercoating finishes over the past 3 years has tripled. Globally, textures are proving to be popular with both architects and fabricators alike. Damage resistance and the forgiving nature of the surface are key features for the fabricators while the feel and the appearance of the texture make the surface more organic for architectural design. Textured surfaces' popularity is gaining momentum across the globe.

AUSTRALIA
e: salesoz@interpon.com
www.interpon.com.au
www.specifyinterpon.com.au

Tel: 1800 630 516
Fax: 1800 650 786

NEW ZEALAND
e: salesnz@interpon.com
www.interpon.co.nz

Tel: 0800 150 527
Fax: 0800 809 679



green building council australia
MEMBER 2017-2018


Interpon D1000 Textura®: Stock Range



Textura® White GA330A



Textura® Primrose GD331A



Textura® Surfmist GA336A




Textura® Paperbark GD314A



Textura® Dune GL352A




Textura® Woodland Grey GL333A



Textura® Silver GY35LA



Textura® Ironstone GL336A



Textura® Jasper GM314A



Textura® Deep Ocean GJ301A



Textura® Monument GL329A



Textura® Black GN305A

For more information please refer to the Interpon Textura Technical Data Sheet or contact our Customer Service Team on 1800 630 516 or salesoz@interpon.com.



Interpon®

DISCLAIMER

AkzoNobel endeavours to ensure the information contained in this publication is correct at the time of printing. All products referred to and any technical advice provided is subject to the standard terms and conditions of sale of the AkzoNobel supplying company. Unless otherwise agreed by us in writing, any contract to purchase products referred to in this color card and any advice that we give in connection with the supply of products are subject to our standard conditions of sale. Typical end uses for Interpon products are displayed in this publication using actual projects and representative images. Textura® is a registered trademark of Akzo Nobel Pty Limited. Interpon® is a registered trademark of Akzo Nobel International BV. © Copyright 2017 Akzo Nobel Pty Limited
ABN 59 000 119 424.

July 2018